

# **BELIEVE YOUR EYES**

# FULLY AUTOMATIC, PRECISION OPTIC FIBER CLEAVER ONE-STEP, INTELLIGENT CLEAVER W/ AUTO BLADE ROTATION & HEIGHT ADJUSTMENT

- A Single-Action Operation
- •Auto Blade Rotation w/ max. 60,000 cleaves
- Digital Cleave Counter w/ Auto Trash Bin
- · Drop-proof and Lightweight Design
- Maintenance Free Cleaver



# AUTO BLADE ROTATION



Blade rotates automatically after each cleaves in 30 channels

# DIGITAL COUNTER



Cleave counts are indicated in real-time in a digital format



# DESCRIPTION

V11 aims to be the most accurate and advanced cleaver produced in the market. The cleaves are made in a single, swift action (One-step) with fully automatic blade rotation and height adjustment after each cleaves to ensure the best cleave results are produced. V11 is equipped with a universal holder, applicable to 250µm fiber cable, 900µm fiber cable, flat cable, ribbon fiber, and jumper cable. It also has an automatic collector for fiber shards and offcuts. Cleaving over 60,000 times, the V11 remains to be completely maintenance-free.

#### **Universal Holder**





**Automatic Fiber Collector** 



Equipped with automatic shard collector

## **TECHNICAL SPECIFICATIONS**

Items	Specifications	
Model	V11	
Туре	Single fiber and Ribbon fiber	
Cladding Diameter	125µm	
Cleaved Length	Single Fiber : 5mm ~ 24mm (Coating diameter $\le$ 250µm) , 10mm ~ 20mm (Coating diameter >250µm) Ribbon (Multi) Fiber : 10mm	
Applicable Fiber Cable	Single Fiber : 160µm to 900µm, 2mm ~ 3mm and drop cable Ribbon (Multi) Fiber : 2 ~ 16 ribbon fibers	
Typical Cleaved Angle	Single Fiber : 0.3 ° ~ 0.8 ° Ribbon (Multi) Fiber : 0.3 ° ~ 1.0 °	
Typical Blade Life	Total 60,000 fiber cleaves (2,000 cleaving per each point, total 30 points)	
Holder	Universal holder, Replaceable holder	
Weight	245g (with Auto Trashbin) / 220g (with Side Cover)	
Dimension	105L x 109W x 52H mm (with Auto Trash Bin) / 87L x 105W x 52H mm (with Side Cover)	
Operation Condition	Temperature: -10 ~ 50 °C / Humidity: 0 ~ 95%RH (non-dew)	
Storage Condition	Temperature: -40 ~ 80 °C / Humidity: 0 ~ 95%RH (non-dew)	
Battery	Coin type Lithium battery CR1220	

## **STANDARD PACKAGE**

Model / Part No.	Description	
CC-04	Cleaver Case	1ea
SC-V11-01	Side Cover	1ea
CB-02	Brush	1ea
CW-03	Hexagonal Wrench	1ea
	Operation Manual	1ea

## **OPTIONAL ACCESSORIES**

Model / Part No.	Description	
B-80	Cleaver Blade	1ea
CH-01	Cleaver Holder	1ea
CM-01	Clamp Module	1ea
TK02-MP01	Stripper	1ea

## SIZE · WEIGHT · PACKAGE



Height: 2.05 inches (52 mm) Width: 4.29 inches (109 mm) Depth: 4.13 inches (105 mm) Weight: 0.54 pounds (245 grams) \*With Auto Trashbin



The Information on this catalog is subject to change without prior notice.



Copyright ⓒ 2020 INNO Instrument Inc. All rights reserved. INNO Instrument Europe GmbH Gothaer Strasse 18, 40880, Germany **tel** +49 2102 9424 8250 **email** chad@innoinstrument.com Printed in Korea

Homepage www.innoinstrument.eu

Please visit us on Facebook www.facebook.com/innoinstrument